

## ► S88 SERIES OXYGEN AND HYDROGEN SOLENOID VALVES

### APPLICATIONS



### GENERAL FEATURES

<b>SERIES</b>	S88
<b>CONNECTION SIZE</b>	1/8" ... 2" BSP (NPT on request)
<b>BODY MATERIAL</b>	Brass (Core tube, plunger: Stainless Steel)
<b>DIAPHRAGM MATERIAL</b>	EPDM (Purify from oil)
<b>WORKING TEMPERATURE</b>	-10...140 °C
<b>WORKING PRESSURE</b>	0 ... 16 bar / 0.5 ... 16 bar / 0.5 ... 12 bar
<b>POSITION</b>	Normally Closed (N.C.) / Normally Open (N.O.)
<b>COIL VOLTAGE</b>	230V AC, 110V, 48V, 24V, 12V AC/DC
<b>PROTECTION CLASS</b>	IP 65, IP 68, Ex-proof Coil



## ► S91 SERIES PISTON TYPE SOLENOID VALVE

### APPLICATIONS



### GENERAL FEATURES

<b>SERIES</b>	S91
<b>CONNECTION SIZE</b>	1/8" ... 1"
<b>BODY MATERIAL</b>	Brass (Core tube, plunger: Stainless Steel)
<b>DIAPHRAGM MATERIAL</b>	TEFLON + NBR, TEFLON + FKM
<b>WORKING PRESSURE</b>	2 ... 70 bar
<b>POSITION</b>	Normally Closed (N.C.) / Normally Open (N.O.)
<b>COIL VOLTAGE</b>	230V AC, 110V, 48V, 24V, 12V AC/DC
<b>PROTECTION CLASS</b>	IP 65, IP 68, Ex-proof Coil

