GV1G09

TeSys GV2, TeSys D & TeSys U - terminal block - 3P - from the top

Product availability: Stock - Normally stocked in distribution facility



Main				
Commercial Status	Commercialised			
Range	Linergy			
Product name	FT			
Device short name	GV1G			
Product or component type	Terminal block			
Accessory / separate part category	Connection accessory			
Poles description	3P			
Range compatibility	TeSys - LS1 TeSys - U TeSys - K TeSys - D TeSys - GV2			

-							
C	^	m	n	m	n	ta	m

[le] rated operational current	63 A			
Mounting location	Тор			
IP degree of protection	IP20 according to IEC 60529			
[Ui] rated insulation voltage	690 V according to IEC 60947-1			
Connections - terminals	Screw clamp terminals 1 flexible AWG 4 Screw clamp terminals 2 cable(s) 00.01 in² (2.54 mm²) flexible without Screw clamp terminals 2 cable(s) 00.01 in² (1.56 mm²) solid Screw clamp terminals 2 cable(s) 00 in² (1.52 mm²) flexible with Screw clamp terminals 1 cable(s) 00.04 in² (1.525 mm²) solid Screw clamp terminals 1 cable(s) 00.02 in² (1.516 mm²) flexible with Screw clamp terminals 1 cable(s) 00.02 in² (1.510 mm²) flexible with Screw clamp terminals 1 solid AWG 4			
ightening torque 19.47 lbf.in (2.2 N.m) - on connector 15.04 lbf.in (1.7 N.m) - on screw clamp terminals				
Product weight	0.09 lb(US) (0.04 kg)			

Ordering and shipping details

Category	22366 - MAN STR PROTECTORS-GV1/GV3			
Discount Schedule	l11			
GTIN	00785901157502			
Nbr. of units in pkg.	1			
Package weight(Lbs)	0.12			
Product availability	Stock - Normally stocked in distribution facility			
Returnability	Υ			
Country of origin	MA			

Contractual warranty

our manary				
Period	18 months			