# XESP10315

Limit switch contact block, Limit switches XC Standard, XESP, 2 C/O snap action, staggered, silver plated



### Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch contact block
Device short name	XESP
Associated body	ZC2JC45
Number of poles	2
Contact operation	Snap action, staggered
Contacts type and composition	2 C/O

## Complementary

XC2J	
Screw-clamp terminals, clamping capacity: 1 x 0.752 x 1.5 mm <sup>2</sup>	
Za	
Silver plated contacts	
Without	
0.01 mm/s	
A300, AC-15 (Ue = 240 V), Ie = 3 A conforming to EN/IEC 60947-5-1 appendix A Q300, DC-13 (Ue = 250 V), Ie = 0.27 A conforming to EN/IEC 60947-5-1 appendix A	
25 mOhm conforming to IEC 60255-7 category 3	
500 V conforming to IEC 60947-5-1 300 V conforming to CSA C22.2 No 14	
10 A cartridge fuse, type gG	
5000000 Cycles, DC-13 120 V, 4 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 10 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C	

### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.2 cm	
Package 1 Width	3.5 cm	
Package 1 Length	4.5 cm	
Package 1 Weight	37.0 g	

# Offer Sustainability

Sustainable offer status	Green Premium product  No need of specific recycling operations  WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
Circularity Profile		
California proposition 65		
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com	

Contractual warranty

Warranty 18 months

