



### Main

Device application	Distribution
Range	Acti 9
Product name	Acti 9 iC60
Product or component type	Miniature circuit-breaker
Device short name	IC60N
Poles description	1P
Number of protected poles	1
[In] rated current	6 A
Network type	DC AC
Trip unit technology	Thermal-magnetic
Curve code	B
Breaking capacity	10 kA Icu conforming to EN/IEC 60947-2 - 220...240 V AC 50/60 Hz 20 kA Icu conforming to EN/IEC 60947-2 - 100...133 V AC 50/60 Hz 6000 A Icn conforming to EN/IEC 60898-1 - 230 V AC 50/60 Hz 10 kA Icu conforming to EN/IEC 60947-2 - 60...72 V DC 15 kA Icu conforming to EN/IEC 60947-2 - 12...60 V DC 36 kA Icu conforming to EN/IEC 60947-2 - 12...60 V AC 50/60 Hz
Utilisation category	Category A conforming to EN 60947-2 Category A conforming to IEC 60947-2
Suitability for isolation	Yes conforming to EN 60947-2 Yes conforming to IEC 60947-2 Yes conforming to EN 60898-1 Yes conforming to IEC 60898-1
Standards	IEC 60898-1 EN 60947-2 IEC 60947-2 EN 60898-1

### Complementary

Network frequency	50/60 Hz
-------------------	----------

Magnetic tripping limit	4 x In +/- 20 %
[Ics] rated service breaking capacity	10 kA 100 % x Icu conforming to EN 60947-2 - 72 V DC 10 kA 100 % x Icu conforming to IEC 60947-2 - 72 V DC 6000 A 100 % x Icu conforming to IEC 60898-1 - 230 V AC 50/60 Hz 15 kA 100 % x Icu conforming to EN 60947-2 - 12...60 V DC 15 kA 100 % x Icu conforming to IEC 60947-2 - 12...60 V DC 6000 A 100 % x Icu conforming to EN 60898-1 - 230 V AC 50/60 Hz 27 kA 75 % x Icu conforming to EN 60947-2 - 12...60 V AC 50/60 Hz 7.5 kA 75 % x Icu conforming to EN 60947-2 - 220...240 V AC 50/60 Hz 27 kA 75 % x Icu conforming to IEC 60947-2 - 12...60 V AC 50/60 Hz 7.5 kA 75 % x Icu conforming to IEC 60947-2 - 220...240 V AC 50/60 Hz 15 kA 75 % x Icu conforming to IEC 60947-2 - 100...133 V AC 50/60 Hz 15 kA 75 % x Icu conforming to EN 60947-2 - 100...133 V AC 50/60 Hz
Limitation class	3 conforming to EN 60898-1 3 conforming to IEC 60898-1
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to IEC 60947-2 500 V AC 50/60 Hz conforming to EN 60947-2
[Uimp] rated impulse withstand voltage	6 kV conforming to EN 60947-2 6 kV conforming to IEC 60947-2
Contact position indicator	Yes
Control type	Toggle
Local signalling	Trip indicator
Mounting mode	Fixed
Mounting support	DIN rail
Comb busbar and distribution block compatibility	YES top or bottom
9 mm pitches	2
Height	85 mm
Width	18 mm
Depth	78.5 mm
Product weight	0.215 kg
Colour	White
Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Connections - terminals	Single terminal, top or bottom rigid wire(s) 1...25 mm <sup>2</sup> max Single terminal, top or bottom flexible wire(s) 1...16 mm <sup>2</sup> max
Wire stripping length	14 mm top or bottom
Tightening torque	2 N.m top or bottom
Earth-leakage protection	Without

## Environment

IP degree of protection	IP20 conforming to EN 60529 IP20 conforming to IEC 60529
Pollution degree	3 conforming to EN 60947-2 3 conforming to IEC 60947-2
Overvoltage category	IV
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % ( 55 °C )
Operating altitude	0...2000 m
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...85 °C

Text

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold

Reference not containing SVHC above the threshold

---

Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

---

### Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---