



Main

| | |
|---------------------------|----------------|
| Range | PratiKa |
| Product or component type | Socket |
| Device short name | PratiKa socket |
| Plug, socket category | Low voltage |
| Poles description | 3P + N + E |
| Network type | AC |
| Outlet standard | Industrial |

Complementary

| | |
|-------------------------------------|--|
| Mounting mode | Wall-mounted |
| Plug, socket, control station shape | Angled |
| [In] rated current | 16 A |
| [Ue] rated operational voltage | 380...415 V |
| Network frequency | 50/60 Hz |
| Ground lug clockwise position | 6 h |
| Plug, socket material | Self-extinguishing engineering polymer housing : |
| Contacts material | Brass sleeves : |
| Connections - terminals | Captive screws |
| Cable cross section | 1...4 mm ² |
| Cable outer diameter | 21 mm |
| Thread type | M25 |
| Product weight | 0.27 kg |
| Height | 120 mm |
| Width | 90 mm |
| Depth | 116 mm |
| Colour | Grey (RAL 7035) |
| Voltage colour | Red |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC 60309-1 IEC 60309-2 |
| IP degree of protection | IP44 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to EN 62262 |
| Fire resistance | 750 °C conforming to IEC 60695-2-1 |
| Relative humidity | 50 % (40 °C) 70 % (30 °C) 90 % (20 °C) |
| Ambient air temperature for operation | 35 °C (86400 s) |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|