


Profile

- Designed for large diameters
- Hollow shaft, max. Ø 30 mm
- Counter with 5 decades and fine reading
- Display can be designed for "mm" or "inch"
- Magnifying function for good readability
- Stainless-steel driving shaft as an option
- Axial seal, dustproof and splash-proof



Mechanical data

Feature	Technical data	Additional information
Housing	reinforced plastic	
Sight window	plastic	mineral glass as an option
Counter	5 decades, fine reading	
Digit height	~7 mm	
Weight	0.1 kg	

Max. speed

Display (after 1st revolution)	max. speed [rpm]
00010	500 (1500)
00015	500 (1000)
00020	500 (750)
00025	500 (600)
00030	500
00040	375
00050	300
00060	250
00080	180
00100	150

Formula:

$$\text{max. speed} = \frac{15000}{\text{indication after 1st revolution}}$$

! Speeds >500 rpm must only be run for short periods.

Ambient conditions

Feature	Technical data	Additional information
Ambient temperature	0 ... 80 °C	

Order

Ordering information

Display	Mounting position				Counting direction
	12	14	16	17	

Hint: Texts highlighted in orange color are ordering features

Ordering table

Feature	Ordering data	Specification	Additional information
Mounting position	... A	12, 14, 16, 17	see the icons illustrating the mounting positions
Indication after 1st revolution	... B	6/5, 10, 15, 17/5, 20, 25, 30, 39/4, 40, 50, 60, 80, 100 others on request	/5 = arithmetical value not displayed
Decimal place	0 C 1 2 3 4	0 = 00000 1 = 0000.0 2 = 000.00 3 = 00.000 4 = 0.0000	
Counting direction	i D e	clockwise ascending values counter-clockwise ascending values	
Hollow shaft/diameter	... E	30, 25 VA30 RH10, RH12, RH14, RH16, RH20, RH25	stainless steel reducing bushes
Hollow shaft/design	WK F WL	hollow shaft short hollow shaft long	not with hollow shaft/diameter "25" only with hollow shaft/diameter "25"
Torque pin/position	I G II	position I position II	
Color	0 H S	orange RAL 2004 black RAL 9005	
Axial seal	OAD I AD	without axial seal with axial seal	

Order key

DA10 - A - B - C - D - E - F - A - G - H - K - I - BP

Scope of delivery: DA10



Accessories:
Reduction sleeve RH

www.siko-global.com