

Micro segnalatori luminosi a led integrati

Led integrated micro luminous signals

Luce fissa

Continuous light




LD SP F
LDSPF
50 49

V	12 - 24 - 48 - 110 - 240 (±10%)			50/60 Hz	IP 66	
°C	-30 +50	On		1 2 3 4 5 6	PC	autoestinguente self-extinguishing

V		12	24	48	-	-
V					110	240
mA		20	20	20	35	30
mA		20	20	20	35	30

LDSPF12DA1	38051	LDSPF24DA3	38063	LDSPF48DA5	38075	LDSPF240A1	38091
LDSPF12DA2	38052	LDSPF24DA4	38064	LDSPF48DA6	38076	LDSPF240A2	38092
LDSPF12DA3	38053	LDSPF24DA5	38065	LDSPF110A1	38081	LDSPF240A3	38093
LDSPF12DA4	38054	LDSPF24DA6	38066	LDSPF110A2	38082	LDSPF240A4	38094
LDSPF12DA5	38055	LDSPF48DA1	38071	LDSPF110A3	38083	LDSPF240A5	38095
LDSPF12DA6	38056	LDSPF48DA2	38072	LDSPF110A4	38084	LDSPF240A6	38096
LDSPF24DA1	38061	LDSPF48DA3	38073	LDSPF110A5	38085		
LDSPF24DA2	38062	LDSPF48DA4	38074	LDSPF110A6	38086		




Kg. 0,026

Luce lampeggiante


Flashing light



LD SP L
LD SPL
50 49

V 12  -24  -48  -110 ~240 ~ (±10%)						 50/60 Hz		Flash/min. 110±20	
IP 66		°C -30 +50	On 			PC		autoestinguente self-extinguishing	

LD SPL12DA1	38171	LD SPL24DA3	38183	LD SPL48DA5	38195	LD SPL240A1	38211
LD SPL12DA2	38172	LD SPL24DA4	38184	LD SPL48DA6	38196	LD SPL240A2	38212
LD SPL12DA3	38173	LD SPL24DA5	38185	LD SPL110A1	38201	LD SPL240A3	38213
LD SPL12DA4	38174	LD SPL24DA6	38186	LD SPL110A2	38202	LD SPL240A4	38214
LD SPL12DA5	38175	LD SPL48DA1	38191	LD SPL110A3	38203	LD SPL240A5	38215
LD SPL12DA6	38176	LD SPL48DA2	38192	LD SPL110A4	38204	LD SPL240A6	38216
LD SPL24DA1	38181	LD SPL48DA3	38193	LD SPL110A5	38205		
LD SPL24DA2	38182	LD SPL48DA4	38194	LD SPL110A6	38206		



Kg. 0,026

Installazione ad incasso foro Ø 12 mm. Fornito adattatore per foro Ø 16 mm - Ø 22 mm.
Flush mount in Ø 12 mm holes. Supplied with adapter for Ø 16 mm - Ø 22 mm holes.

Per ordinare l'opzione nera richiedere i codici. Code numbers for the black version are available on request.

Mini luci a led integrati

Led integrated mini beacons

Luce fissa

Continuous light




LD MINI OVO F
LD MINIOVOF
49 50

V	24 - 110 - 240 (±10%)			50/60 Hz	IP 66	
°C	-30 +50	On		1 2 3 4 5 6	PC	autoestinguente self-extinguishing

V		24	-	-
V			110	240
mA		55	60	45
mA		50	60	45

LD MINIOVOF24DA1	31601	LD MINIOVOF110A1	31611	LD MINIOVOF240A1	31621
LD MINIOVOF24DA2	31602	LD MINIOVOF110A2	31612	LD MINIOVOF240A2	31622
LD MINIOVOF24DA3	31603	LD MINIOVOF110A3	31613	LD MINIOVOF240A3	31623
LD MINIOVOF24DA4	31604	LD MINIOVOF110A4	31614	LD MINIOVOF240A4	31624
LD MINIOVOF24DA5	31605	LD MINIOVOF110A5	31615	LD MINIOVOF240A5	31625
LD MINIOVOF24DA6	31606	LD MINIOVOF110A6	31616	LD MINIOVOF240A6	31626



Kg. 0,047

Luce lampeggiante


Flashing light



LD MINI OVO L
LD MINIOVOL
49 50

V 24  -110 ~ -240  (±10%)				==		 50/60 Hz		Flash/min. 150±20				
IP 66		°C -30 +50	On 		1	2	3	4	5	6	PC	autoestinguente self-extinguishing

LD MINIOVOL24DA1	31631	LD MINIOVOL110A1	31641	LD MINIOVOL240A1	31651
LD MINIOVOL24DA2	31632	LD MINIOVOL110A2	31642	LD MINIOVOL240A2	31652
LD MINIOVOL24DA3	31633	LD MINIOVOL110A3	31643	LD MINIOVOL240A3	31653
LD MINIOVOL24DA4	31634	LD MINIOVOL110A4	31644	LD MINIOVOL240A4	31654
LD MINIOVOL24DA5	31635	LD MINIOVOL110A5	31645	LD MINIOVOL240A5	31655
LD MINIOVOL24DA6	31636	LD MINIOVOL110A6	31646	LD MINIOVOL240A6	31656



Kg. 0,047

Installazione ad incasso foro Ø 12 mm. Fornito adattatore per foro Ø 16 mm - Ø 22 mm.
Flush mount in Ø 12 mm holes. Supplied with adapter for Ø 16 mm - Ø 22 mm holes.