XZCC12FCM50B

Female, M12, 5 pin, elbowed connector, cable gland Pg 7



Main Range of product Telemecanique Cabling components Accessory / separate Cabling accessories part categor Accessory / separate Connector part type Electrical connection Elbowed female connector M12, 5 pins Collar material Metal Status LED Without Cable connection Screw terminal / wire size <0.75 mm² / clamping capacity 3...6 mm

$c_{\alpha m}$		nont	on
Com	pien	ш	aı y

Cable gland type	Pg 7	
Cable connector fixing	Screw-on	
[Ue] rated operational voltage	30 V AC 36 V DC	
[In] rated current	3 A	
Enclosure material	Plastic	
Minimum insulating resistance	1000 GΩ	
Contact resistance	8000 μOhm	
Net weight	0.02 kg	

Environment

IP degree of protection	IP67
Ambient air temperature for operation	-4085 °C

Packing Units

3 - 3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 cm
Package 1 Width	11.500 cm
Package 1 Length	14.000 cm
Package 1 Weight	29.000 g
Unit Type of Package 2	S01
Number of Units in Package 2	50
Package 2 Height	15.000 cm
Package 2 Width	15.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	1.636 kg

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty


Warranty 18 months



Product data sheet Dimensions Drawings

XZCC12FCM50B

Dimensions



(1) Cable gland : no. 7 plastic (Pg 7)

Product data sheet Connections and Schema

XZCC12FCM50B

Connections and Schemes

